



Product fiche iV14-Zero according to VO 1254/2014 EU, dated 2014-07-11

Pt.	Description	Data	
a	Supplier's name	inVENTer GmbH	
b	Supplier's model identifier	iV14-Zero iV14-Zero Comer	
c	SEC class / Specific energy consumption [kWh/(m ² a)]	cold	-88.068
		average	A+
		warm	-18.678
d	Typology	BVU	
e	Type of drive installed	2	
f	Type of heat recovery system	regenerative	
g	Thermal efficiency of heat recovery η_t [%]	87	
h	Maximum flow rate (supply air) [m ³ /h]	58	
i	Electric power input [W]	6	
j	Sound power level L_{wa} [dB (A)]	37	
k	Reference flow rate [m ³ /h]	42	
l	Reference pressure difference [Pa]	0	
m	SPI [W/m ³ /h]	0,15	
n	Control factor	0.65	
o	Internal/external leakage rate [%]	n. a.	
p	Mixing rate [%]	n. a.	
q	Position of visual filter warning	Controller	
r	Regulated supply and exhaust grilles in the facade (one-direction devices only)	no	
s	Internet adress	Homepage: www.inventer.de	
t	Airflow sensitivity [%]	29.4	
u	Indoor and outdoor air tightness [m ³ /h]	6.3	
v	Annual electricity consumption [kWh/(m ² a)]	0,87	
w	Annual heating saved [kWh/(m ² a)]	cold	90.25
		average	46.13
		warm	20.86



Product fiche iV14-Zero according to VO 1254/2014 EU, dated 2014-07-11


Pt.	Description	Data	
a	Supplier's name	inVENTer GmbH	
b	Supplier's model identifier	iV14-Zero iV14-Zero Comer	
c	SEC class / Specific energy consumption [kWh/(m ² a)]	cold	-82.062
		average	A
		warm	-14.995
d	Typology	BVU	
e	Type of drive installed	2	
f	Type of heat recovery system	regenerative	
g	Thermal efficiency of heat recovery η_t [%]	87	
h	Maximum flow rate (supply air) [m ³ /h]	58	
i	Electric power input [W]	6	
j	Sound power level L_{wa} [dB (A)]	37	
k	Reference flow rate [m ³ /h]	42	
l	Reference pressure difference [Pa]	0	
m	SPI [W/m ³ /h]	0,15	
n	Control factor	1	
o	Internal/external leakage rate [%]	n. a.	
p	Mixing rate [%]	n. a.	
q	Position of visual filter warning	Controller	
r	Regulated supply and exhaust grilles in the facade (one-direction devices only)	no	
s	Internet adress	Homepage: www.inventer.de	
t	Airflow sensitivity [%]	29.4	
u	Indoor and outdoor air tightness [m ³ /h]	6.3	
v	Annual electricity consumption [kWh/(m ² a)]	2.07	
w	Annual heating saved [kWh/(m ² a)]	cold	87.23
		average	44.59
		warm	20.16



ENERG Y UA
енергия · ενέργεια IE IA

INVENTER

iV14-Zero;
iV14-Zero Corner



Local demand control	Manual control
MZ-Home sMove w/ Sensorik	sMove w/o Sensorik
A+	A

37
dB (A)

58 m³/h